



DGR15-1900-04L



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS

MAX. PRESSURE	4.0MPa; (40Bar)
MAX. SPEED	3500RPM;
TEMPERATURE	-30℃-----+120℃
MEDIA TYPE 介质	热水/冷却水/压缩空气/油品
	water/Hot water/air/oil

备注：技术参数数据为最大值,并不能同时使用;
The technical parameter data is the maximum value and cannot be used at the same time.

使用参数 Working parameters

介质 Fluid	压力 Pressure	温度 Temperature	转速 Rotating speed
空气 Air	1.0MPa;	-30℃-----+120℃	3000RPM
水 Water	1.1MPa;	-30℃-----+120℃	3000RPM
Double high-precision groove ball bearings for high stability. Balanced mechanical sealing structure for prolonged service life. Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.			



订货编号 Order-No.

Copper 铜壳	Aluminum 铝壳	Stainless 不锈钢壳
DGR15-1901-04L	DGR15-1902-04L	DGR15-1903-04L
适用介质：水/热水/油品等 Applicable medium: water/hot water/oil	适用介质：压缩空气/液压油等 Applicable medium: compressed air hydraulic oil	适用介质：冷却水/切削液 Applicable medium: water/cutting fluid

旋转接头 Rotary joint E-mail: sddeweier88@163.com		 德威迩 www.sddeweier.com
	TEL: +86 632 5822778 TEL: +86 632 5832779	P/N: DGR15-1900-04L