



DGR20-1900-03R



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS

MAX. PRESSURE	4.0MPa; (<40Bar)
MAX. SPEED	3500RPM;
TEMPERATURE	-30℃----+120℃
MEDIA TYPE 介质	热水/冷却水/压缩空气/油品
	water/Hot water/air/oil

备注：技术参数数据为最大值,并不能同时使用;
The technical parameter data is the maximum value and cannot be used at the same time.

使用参数 Working parameters

介质 Fluid	压力 Pressure	温度Temperature	转速 Rotating speed
空气 Air	1.0MPa;	-30℃----+120℃	3000RPM
水 Water	1.1MPa;	-30℃----+120℃	3000RPM
Double high-precision groove ball bearings for high stability. Balanced mechanical sealing structure for prolonged service life. Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.			



订货编号 Order-No.

Copper 铜壳	Aluminum 铝壳	Stainless 不锈钢壳
DGR20-1901-03R	DGR20-1902-03R	DGR20-1903-03R
适用介质: 水/热水/油品等 Applicable medium: water/hot water/oil	适用介质: 压缩空气/液压油等 Applicable medium: compressed air hydraulic oil	适用介质: 冷却水/切削液 Applicable medium: water/cutting fluid

旋转接头 Rotary joint E-mail: sddeweier88@163.com		 www.sddeweier.com
	TEL: +86 632 5822778 TEL: +86 632 5832779	P/N: DGR20-1900-03R