


6



CH 41




德威迩

[illegible]

1" B2D

 $\phi_{1.7}$

Q



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS

使用参数 Working parameters			
介质 Fluid	压力 Pressure	温度 Temperature	转速 Rotating speed
空气 Air	1.0MPa:	-30℃----+120℃	2800RPM
水 Water	1.1MPa:	-30℃----+120℃	2800RPM

- Double high-precision groove ball bearings for high stability.
- Balanced mechanical sealing structure for prolonged service life.
- Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.


备注：技术参数数据为最大值，并不能同时使用；
The technical parameter data is the maximum value and cannot be used at the same time.



订货编号 Order-No.

Copper 铜壳	Aluminum 铝壳	Stainless 不锈钢壳
DGR25-1901-03R	DGR25-1902-03R	DGR25-1903-03R
适用介质: 水/ 热水/ 油品等 Applicable medium: water/hot water/oil	适用介质: 压缩空气/ 液压油等 Applicable medium: compressed air hydraulic oil	适用介质: 冷却水/ 切削液 Applicable medium: water/cutting fluid

<p>旋转接头 Rotary joint</p> <p>E-mail: sddeweier88@163.com</p>	<p> DEWEIER 德威迩</p> <p>www.sddeweier.com</p>
---	---



TEL : +86 632 5822778
TEL : +86 632 5832779

P/N:DGR25-1900-03R

6