



DGR50-1900-03R



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS

MAX. PRESSURE	1.6MPa; (<16Bar)
MAX. SPEED	750RPM;
TEMPERATURE	-30℃----+120℃
MEDIA TYPE 介质	water/Hot water/air/oil
	热水/冷却水/压缩空气/油品

使用参数 Working parameters

介质 Fluid	压力 Pressure	温度 Temperature	转速 Rotating speed
空气 Air	1.0MPa;	-30℃----+120℃	500RPM
水 Water	1.1MPa;	-30℃----+120℃	750RPM
Double high-precision groove ball bearings for high stability. Balanced mechanical sealing structure for prolonged service life. Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.			

备注：技术参数数据为最大值,并不能同时使用;

The technical parameter data is the maximum value and cannot be used at the same time.

订货编号 Order-No.

Copper 铜壳	Aluminum 铝壳	Stainless 不锈钢壳
DGR50-1901-03R	DGR50-1902-03R	DGR50-1903-03R
适用介质: 水/ 热水/ 油品等 Applicable medium: water/hot water/oil	适用介质: 压缩空气/ 液压油等 Applicable medium: compressed air hydraulic oil	适用介质: 冷却水/ 切削液 Applicable medium: water/cutting fluid

<b>旋转接头</b> Rotary joint E-mail: sddeweier88@163.com		 www.sddeweier.com
	TEL : +86 632 5822778 TEL : +86 632 5832779	P/N:DGR50-1900-03R