

### 单转盘旋转接头—法兰型





单转盘法兰盘型的主体安装部呈法兰盘形状, 降低了整体高度, 结构紧凑。

6回路+1中央供给口，各回路可独立使用。  
 请通过座垫式配管从主体法兰盘侧供油。

### Single turntable rotary joint - flange type

The main body mounting portion of the single turntable flange type has a flange shape, which reduces the overall height and is compact. 6 loop + 1 central supply port, each circuit can be used independently.

Please supply oil from the side of the main flange  
by seat-type piping.



技术参数表 Operating Parameter	
最高压力 Max. pressure:	25MPa;
最高转速 Max. speed:	120RPM.
使用温度 Operating temperature:	-20℃—+80℃
适用介质 Fluid use:	液压油/冷却水/压缩空气 Hydraulic oil /water/air
技术参数数据为最大值，不能同时使用； The technical parameter data is the maximum value and cannot be used at the same time;	



						Rotary joint			枣庄市德威逊机械科技有限公司		
标记	处数	分区	更改文件号	签名	年、月、日	阶段标记			重量	比例	液压旋转接头
设计	Andy Yu	2015-10-31	标准化								
											DRBF0610-Rc1/4''
审核										1:1.5	
工艺			批准			共 1 张			第 1 张		