


### 单转盘旋转接头—法兰型

单转盘法兰盘型的主体安装部呈法兰盘形状，降低了整体高度，结构紧凑。  
8回路+1中央供给口，各回路可独立使用。  
请通过座垫式配管从主体法兰盘侧供油。

### Single turntable rotary joint - flange type


The main body mounting portion of the single turntable flange type has a flange shape, which reduces the overall height and is compact.  
8 loop + 1 central supply port, each circuit can be used independently.  
Please supply oil from the side of the main flange by seat-type piping.



停止侧  
Stop side

旋转侧  
Rotating side

技术参数表 Operating Parameter	
最高压力 Max. pressure:	25MPa
最高转速 Max. speed:	100RPM
使用温度 Operating temperature:	-20℃~+80℃
使用介质 Fluid used:	液压油/冲油/压缩空气 Hydraulic oil /air/oil
技术参数数据为最大值，不能同时使用！ The technical parameter data is the maximum value and cannot be used at the same time!	



				Rotary joint			枣庄市德威迩机械科技有限公司	
标记	处数	分区	更改文件号	签名	年、月、日	阶段标记	重量	比例
设计	Andy Yu	2015-10-31	标准化					1:1
审核								
工艺			批准			共 1 张	第 1 张	
							液压旋转接头	
							DRBF0810-Rc1/4'	