



DRF03010H10



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS

使用参数 Working parameters

MAX. PRESSURE	32MPa; (320Bar)	介质 Fluid	空气 Air	压力 Pressure	2.0MPa;	温度 Temperature	80℃	转速 Rotating speed	150RPM
MAX. SPEED	250RPM;	水 Water		4.0MPa;		80℃		60RPM	
TEMPERATURE	-20℃----+80℃	液压油 Hydraulic oil		7.0MPa;		80℃		50RPM	
				25MPa;		80℃		20RPM	
MEDIA TYPE 介质	Hydraulic oil/water/air	DEWEL DEFO3HJO Series are multi-way rotary joints designed to carry multiple media continuously for low-speed and high-pressure equipment. They are used on machining							
	液压油/冷却水/压缩空气								

备注: 技术参数数据为最大值, 并不能同时使用;
The technical parameter data is the maximum value and cannot be used at the same time.

德威迩公司 DRF03H10 系列旋转接头是一种专门具有多个通孔, 可连续提供多路介质给低速高压旋转设备的一种旋转接头。服务于加工中心旋转工作台、旋转平台、卷取机、转炉、大包回转工作台、液压机械及多通路高压控制阀等设备。
DEWEL DRF03H10 Series are multi-way rotary joints designed to carry multiple media continuously for low-speed and high-pressure equipment. They are used on machining center revolving tables, rotating platforms, coiling machines, converters, ladle turret, hydraulic machinery, multi-way high pressure controller and etc.



德威迩企业官网



德威迩业务号

多通道旋转接头 Multi-Passage Rotary joint E-mail: sddeweier88@163.com		DEWEIER 德威迩 www.sddeweier.com
TEL: +86 632 5822778 TEL: +86 632 5832779		P/N: DRF03010H10-G3/8''