



DRL0125-G1''

2-M12
止转孔Stop turning



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS		使用参数 Working parameters			
MAX. PRESSURE	32MPa; (320Bar)	介质 Fluid	压力 Pressure	温度 Temperature	转速 Rotating speed
MAX. SPEED	300RPM;	空气 Air	2.0MPa;	80℃	150RPM
TEMPERATURE	-20℃----+80℃	水 Water	4.0MPa;	80℃	60RPM
MEDIA TYPE 介质	Hydraulic oil/water/air	液压油 Hydraulic oil	7.0MPa;	80℃	200RPM
	液压油/冷却水/压缩空气		25MPa;	80℃	150RPM
备注：技术参数数据为最大值,并不能同时使用； The technical parameter data is the maximum value and cannot be used at the same time.		德威迩公司 DRL02 系列旋转接头是一种专门具有多个通道，可连续提供多种介质给低速高压旋转设备的一种旋转接头。 服务于加工中心旋转工作台、旋转平台、卷取机、转炉、大包回转工作台、液压机械及多通路高压控制器等设备。 DEWEL DRL02 Series are multi-way rotary joints designed to carry multiple media continuously for low-speed and high-pressure equipment. They are used on machining center revolving tables, rotating platforms, coiling machines, converters, ladle turret, hydraulic machinery, multi-way high pressure controller and etc.			



订货编号 Order-No.		
Aluminum 铝壳	Stainless 不锈钢壳	Steel 碳钢
DRL0125-1802-03R	DRL0125-1803-03R	DRL0125-1805-03R
适用介质：压缩空气/液压油等 Applicable medium: compressed air hydraulic oil	适用介质：冷却水/切削液 Applicable medium: water/cutting fluid	适用介质：液压油 Applicable medium: hydraulic oil
多通道旋转接头 Multi-Passage Rotary joint E-mail: sddeweier88@163.com		 德威迩 www.sddeweier.com
 TEL : +86 632 5822778 TEL : +86 632 5832779		P/N: DRL0125-G1''