





GYZ15-1800-03R



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS		使用参数 Working parameters			
MAX. PRESSURE	35MPa; (350Bar)	介质 Fluid	压力 Pressure	温度 Temperature	转速 Rotating speed
MAX. SPEED	30RPM;	空气 Air	2.0MPa;	80℃	30RPM
TEMPERATURE	-20℃----+80℃	水 Water	16MPa;	80℃	30RPM
MEDIA TYPE 介质	Hydraulic oil/water/air	液压油 Hydraulic oil	35MPa;	80℃	30RPM
备注：技术参数数据为最大值,并不能同时使用； The technical parameter data is the maximum value and cannot be used at the same time.		德威迩公司 GYJ/GYZ 系列旋转接头是用于刚性管道之间回转或消除由于液压元件移动而引起液压软管扭曲、扭矩及压力面设计的一种活动关节。其内部由轴承支撑，旋转扭矩小，专用密封件使用寿命长。 DEWEL GYJ/GYZ Series are swivel joints designed for swiveling application between piping. They are used to eliminate potential hose twisting caused by the movement of hydraulic components. Supported by bearings, the structure can be operated by low rotation torque. High quality sealing parts are used to provide prolonged sealing performance.			

订货编号 Order-No.		
Aluminum 铝壳	Stainless 不锈钢壳	Steel 碳钢
GYZ15-1802-03R	GYZ15-1803-03R	GYZ15-1805-03R
适用介质：压缩空气/液压油等 Applicable medium: compressed air hydraulic oil	适用介质：高压水 Applicable medium: High pressure water	适用介质：液压油 Applicable medium: hydraulic oil
多通道旋转接头 Multi-Passage Rotary joint E-mail: sddeweier88@163.com		 www.sddeweier.com
	TEL : +86 632 5822778 TEL : +86 632 5832779	P/N: GYZ15-1800-03R